

L-1553YDT

YELLOW


### Features

- LOW POWER CONSUMPTION.
- ULTRA BRIGHTNESS IS AVAILABLE.
- WIDE VIEWING ANGLE.
- RELIABLE AND RUGGED.
- EXCELLENT UNIFORMITY OF LIGHT OUTPUT.
- IDEAL AS FLUSH MOUNTED PANEL INDICATORS.
- LONG LIFE - SOLID STATE RELIABILITY.

### Description

The Yellow source color devices are made with Gallium Arsenide Phosphide on Gallium Phosphide Yellow Light Emitting Diode.

### Package Dimensions



#### Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.25(0.01)$  unless otherwise noted.
3. Lead spacing is measured where the lead emerge package.
4. Specifications are subject to change without notice.

## Selection Guide

| Part No.  | Dice               | Lens Type       | Iv (mcd)<br>@ 10 mA |      | Viewing<br>Angle |
|-----------|--------------------|-----------------|---------------------|------|------------------|
|           |                    |                 | Min.                | Typ. | Θ1/2             |
| L-1553YDT | YELLOW (GaAsP/GaP) | YELLOW DIFFUSED | 1                   | 5    | 110°             |

Note:

1. Θ1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.

## Electrical / Optical Characteristics at T<sub>A</sub>=25°C


| Symbol                | Parameter                | Device | Typ. | Max. | Units | Test Conditions            |
|-----------------------|--------------------------|--------|------|------|-------|----------------------------|
| $\lambda_{peak}$      | Peak Wavelength          | Yellow | 590  |      | nm    | I <sub>F</sub> =20mA       |
| $\lambda_D$           | Dominate Wavelength      | Yellow | 588  |      | nm    | I <sub>F</sub> =20mA       |
| $\Delta\lambda_{1/2}$ | Spectral Line Half-width | Yellow | 35   |      | nm    | I <sub>F</sub> =20mA       |
| C                     | Capacitance              | Yellow | 20   |      | pF    | V <sub>F</sub> =0V; f=1MHz |
| V <sub>F</sub>        | Forward Voltage          | Yellow | 2.1  | 2.5  | V     | I <sub>F</sub> =20mA       |
| I <sub>R</sub>        | Reverse Current          | Yellow |      | 10   | uA    | V <sub>R</sub> = 5V        |

## Absolute Maximum Ratings at T<sub>A</sub>=25°C

| Parameter                     | Yellow              | Units |
|-------------------------------|---------------------|-------|
| Power dissipation             | 105                 | mW    |
| DC Forward Current            | 30                  | mA    |
| Peak Forward Current [1]      | 140                 | mA    |
| Reverse Voltage               | 5                   | V     |
| Operating/Storage Temperature | -40°C To +85°C      |       |
| Lead Solder Temperature [2]   | 260°C For 5 Seconds |       |

Notes:

1. 1/10 Duty Cycle, 0.1ms Pulse Width.
2. 2mm below package base.



Yellow

L-1553YDT

