


MEMORY BACKUP BATTERY - LITHIUM



SPECIFICATIONS

| | | |
|-----------------------|---|---|
| Model | : | CR2032-1HS |
| Description | : | Lithium Coin Cell (LiMnO ₂), Mercury Free, RoHS Compliant |
| Nominal Capacity | : | 210mAh at 30K Ohm continuous discharge |
| Nominal Voltage | : | 3.0 V |
| Cut-Off Voltage | : | 2.0 V |
| Approx. Weight | : | 3.4 g |
| Expected Shelf Life | : | 3 years ex-factory |
| Operating Temperature | : | -20 degC to 60 degC |
| Recommended Drain | : | Pulse - 15mA Standard - 0.5mA Low - 0.004mA |
| Service Life | : | 1150 hrs at 15K Ohm continuous discharge 2310 hrs at 30K Ohm continuous discharge |
| Application | : | Memory Backup, Electronic Watches, Calculators, Cameras, Electronic Translators, Low Power Cordless Application |


Typical Discharge Characteristics




Typical Discharge Characteristics



Typical Discharge Characteristics



Typical Discharge Characteristics (Pulse Discharge)



Information is for reference only and is not construed as warranties either expressed or implied, of future performance. Performance varies with time, discharge and storage condition.. 1 year limited guarantee against manufacturing defects. Other problem caused by misuse, mishandling of cell, or malfunction of equipment, is not under the warranty.

Model : CR2032-1HS
Version : 2.50

WELL LINK
INDUSTRIAL LIMITED

F831RB2