



Material
 Screw: M3, Steel, Zn plated
 Shrapnel: Phosphor bronze, Nickel plated
 Pin header: Brass, Tin plated
 Housing: PA66, UL94V-0

Electrical
 Rated voltage: 250V
 Rated current: 16A
 Wire range: 22~14AWG 2.5mm²
 Contact Resistance: 20 mΩ
 Insulation resistance: 500MΩ/DC500V
 Withstand voltage: AC2000V / 1min

Mechanical
 Temp. Range: -40 °C ~ +105 °C
 Soldering: 250 °C 5Sec. Max.
 Torque: 0.5 N.m (4.43Lb. in)
 Strip length: 4.5~5 mm

Order Information

L-KLS2-300 -7.50-XXP-2 S XX

- RoHS
- Terminal Block
- Pitch
- No. of Pole
- Product Code: 00~99
- Screw: S- Slot Screw
- Color: 2- Blue

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	Description:	
X.	±0.60	X.	±5°	UNITS	Screw CONN TERM BLOCK 7.50MM	
.X	±0.38	.X	±3°	SHEET SIZE		A4
.XX	±0.25	.XX	±2°	KLS P/N:		KLS2-300-7.50-XXP-2S
Draw by: Date		2015-09-01				
Check by: Date		2015-09-15				
SCALE		SHEET		OF		

KLS ELECTRONIC CO., LTD.