


Part Number	Maximum Allowable Voltage		Varistor Voltage V@0.1mA		Maximum Clamping Voltage V@ 5A	Withstanding Surge Current		Rated Wattage (W)	Energy 10/1000 s (J)	UL	CSA	VDE
	ACrms (V)	DC (V)	(V)	Tolerance Range		1Time (A)	2 Times (A)					
JVR14N180M87□△△	11	14	18	+ 20%	•36	1000	500	0.1	4.7	✓		✓
JVR14N220L 87□△△	14	18	22	+ 15%	•43				5.4	✓		✓
JVR14N270K87□△△	17	22	27		•53				6.9	✓		✓
JVR14N330K87□△△	20	26	33		•65				8.8	✓		✓
JVR14N390K87□△△	25	31	39		•77				9.4	✓		✓
JVR14N470K87□△△	30	38	47		•93				12.0	✓		✓
JVR14N560K87□△△	35	45	56		•110				14.0	✓		✓
JVR14N680K87□△△	40	56	68		•135				17.0	✓		✓
JVR14N820K87□△△	50	65	82		135				22.0	✓		✓
JVR14N101K78□△△	60	85	100		165				28.0	✓		✓
JVR14N121K87□△△	75	100	120	+10%	200	32.0	✓		✓			
JVR14N151K87□△△	95	125	150		250	44.0	✓		✓			
JVR14N181K87□△△	115	150	180		300	52.0	✓		✓			
JVR14N201K87□△△	130	170	200		340	57.0	✓	✓	✓			
JVR14N221K87□△△	140	180	220		360	62.0	✓	✓	✓			
JVR14N241K87□△△	150	200	240		395	67.0	✓	✓	✓			
JVR14N271K87□△△	175	225	270		455	79.0	✓	✓	✓			
JVR14N301K87□△△	195	250	300		505	84.0	✓	✓	✓			
JVR14N331K87□△△	210	275	330		550	92.0	✓	✓	✓			
JVR14N361K87□△△	230	300	360		595	104.0	✓	✓	✓			
JVR14N391K87□△△	250	320	390		650	120.0	✓	✓	✓			
JVR14N431K87□△△	275	350	430		710	132.0	✓	✓	✓			
JVR14N471K87□△△	300	385	470		775	140.0	✓	✓	✓			
JVR14N511K87□△△	320	418	510		842	148.0	✓	✓	✓			
JVR14N561K87□△△	350	460	560		920	156.0	✓	✓	✓			
JVR14N621K87□△△	385	505	620		1025	164.0	✓	✓	✓			
JVR14N681K87□△△	420	560	680		1120	172.0	✓	✓	✓			
JVR14N751K87□△△	460	615	750		1240	180.0	✓	✓	✓			
JVR14N781K87□△△	485	640	780		1290	184.0	✓	✓	✓			
JVR14N821K87□△△	510	670	820		1355	188.0	✓	✓	✓			
JVR14N911K87□△△	550	745	910	1500	204.0	✓	✓	✓				
JVR14N102K87□△△	625	825	1000	1650	224.0	✓	✓	✓				
JVR14N112K87□△△	680	895	1100	1815	248.0	✓	✓	✓				
JVR14N182K87□△△	1000	1465	1800	2970	348.0							

1) The clamping voltage from 180M to 680K are tested with current 10A.
For application required ratings not shown, contact RFE application engineering.

- : Lead Style
Y: vertical kink (standard)
P: straight leads
- △△ : Lead Length / Packing Method



PULSE RATING CURVES

